

◆ LBB Forced Convection Oven

Excellent uniformity at a moderate price




The Despatch LBB oven features a combination of horizontal and vertical airflow that offers excellent temperature uniformity at a moderate price. It is recommended for a variety of laboratory and production applications including drying, curing, annealing and materials testing.

A top-mounted fan draws air through the heater coils and propels it back to the chamber through plenums in the side walls, resulting in consistent, uniform temperatures. Powerful open coil heating elements and a forward curved fan deliver faster heat-up rates and short processing times. Digital controls regulate temperatures within tight tolerances.

The LBB is designed and manufactured to provide years of dependable service. The fan and heater are top-mounted to prevent damage from spills. When spills do occur, the corrosion-resistant stainless steel interior and nickel plated shelves clean up easily. The motor is permanently lubricated and virtually maintenance free. And Despatch warrants the heater performance for a full five years – the best warranty in the industry.

FEATURES AT A GLANCE

- ◆ Forced convection from top-mounted fan and plenums on sides of chamber
- ◆ Temperatures up to 204° C (400° F)
- ◆ 304 Stainless steel interior
- ◆ Digital control with 3/4" (1.9cm) LED display
- ◆ Nickel plated shelves - by model rated to 50 or 200lbs (23 or 91kg)
- ◆ High-limit control
- ◆ Five year heater warranty
- ◆ UL and C-UL listed



OPTIONS

- ◆ Additional shelves
- ◆ Protocol 3™ programmable control with large LCD display, integrated data logging capabilities and USB port for simple oven set-up and data export
- ◆ Process timer with audible and visual alarm
- ◆ Door with window and interior light
- ◆ Pass-through doors (2-18 and 2-27)
- ◆ 2" access port
- ◆ Oven stand
- ◆ CE compliance

Warning: Not for use with flammable or combustible materials. If your process has flammable solvents, contact Despatch.

LBB	1-23	1-69	2-12	2-18	2-27	
PHYSICAL SPECIFICATIONS						
Chamber size (width x depth x height) <i>*Clear opening width is reducing 1 1/2" (3.8cm) due to 3/4" (1.9cm) shelf supports on each side.</i>	18 x 18 x 12 in. 46 x 46 x 31 cm	30 x 18 x 22 in. 76 x 46 x 56 cm	30 x 20 x 35 in. 77 x 51 x 89 cm	37 x 24 x 35 in. 94 x 61 x 89 cm	37 x 37 x 35 in. 94 x 94* x 89 cm	
Capacity in cubic feet (liters)	2.3 (65)	6.9 (195)	12.1 (343)	18 (510)	27.7 (784)	
Overall size (width x depth x height) <i>*Depth includes exhaust port</i>	24 x 24.5 x 26 in. 61 x 62 x 66 cm	36 x 24.5 x 36.5 in. 91 x 62 x 93 cm	36 x 26.5 x 51.5 in. 91 x 67 x 131 cm	43 x 30.5 x 51.5 in. 109 x 78 x 131 cm	43 x 43.5 x 51.5 in. 109 x 111 x 131 cm	
Electrical: 50/60 hertz - single phase <i>*Oven will run on 208V with a 25% reduction in heater output</i>	Volts*	120 240	120 240	240	240	
	Amps	11.6 5.8	21.6 10.8	16.6 amps	16.7 amps	21.7 amps
	Heater kW	1.2 kW	2.4 kW	3.6 kW	3.6 kW	4.8 kW
Capacity per shelf	50lb/23kg	200lb/91kg	200lb/91kg	200lb/91kg	200lb/91kg	
Maximum number of shelves (Two provided)	5 on 2 in. centers*	5 on 4 in. centers*	8 on 4 in. centers*	8 on 4 in. centers	8 on 4 in. centers	
Cord and plug	15 amp	None - hardwire	None - hardwire	None - hardwire	None - hardwire	
Number of doors	1	2	2	2	2	
Approximate net weight	140 lbs (63 kg)	245 lbs (112 kg)	315 lbs (144 kg)	400 lbs* (182 kg)	550 lbs* (250 kg)	
Approximate shipping weight	205 lbs (92 kg)	320 lbs (146 kg)	385 lbs (175 kg)	485 lbs* (221 kg)	635 lbs* (289 kg)	
FUNCTIONAL SPECIFICATIONS						
Time to temp with no load (40°C to 150°C)	17 minutes	15 minutes	15 minutes	17 minutes	17 minutes	
Time to temp with no load (40°C to 204°C)	30 minutes	26 minutes	30 minutes	33 minutes	33 minutes	
Recovery time after door open 1 min. (150°C)	2 minutes	3 minutes	3 minutes	3 minutes	4 minutes	
Recovery time after door open 1 min. (204°C)	4 minutes	6 minutes	6 minutes	7 minutes	8 minutes	
Temperature uniformity <i>Based on 9 point test in empty oven</i>	+/- 3°C at 150°C +/- 4°C at 204°C	+/- 3°C at 150°C +/- 4°C at 204°C	+/- 3°C at 150°C +/- 4°C at 204°C	+/- 3°C at 150°C +/- 4°C at 204°C	+/- 3°C at 150°C +/- 4°C at 204°C	
Operating range with 20°C ambient	35°C - 204°C	35°C - 204°C	40°C - 204°C	40°C - 204°C	40°C - 204°C	
Control stability	+/- 0.5°C	+/- 0.5°C	+/- 0.5°C	+/- 0.5°C	+/- 0.5°C	
Maximum load capacity	200 lbs. (91 kg)	400 lbs. (181 kg)	600 lbs. (272 kg)	600 lbs.* (272 kg)	600 lbs.* (272 kg)	
Maximum shelf capacity	50 lbs. (23 kg)	200 lbs. (91 kg)	200 lbs. (91 kg)	200 lbs. (91 kg)	200 lbs. (91 kg)	
Exhaust capacity	Adj. to 1 CFM (0.5 lps)	Adj. to 3 CFM (1.4 lps)	Adj. to 12 CFM (5.71 lps)	Adj. to 14 CFM (6.61 lps)	Adj. to 14 CFM (6.61 lps)	

Notes: Uniformity figures are based on a nine-point test conducted in an empty oven after stabilization period. Uniformity can vary slightly depending on unit and operating conditions. Time to temperature, recovery time, and temperature uniformity are based on 240V/60Hz operation, with control panel on top. Actual results may vary slightly depending on unit configuration and operating conditions. Minimum operating temperature is based on 20°C ambient temperature measured at the fresh air inlet with the exhaust air damper fully open. Maximum load capacity figures are only for standard configurations with controls on top. Specifications are subject to change without notice.

SERVICE AND TECHNICAL SUPPORT

service parts: 1-800-473-7373
international service/main: 1-952-469-8230
service fax: 1-952-469-8193
 service@despatch.com
 parts@despatch.com

GLOBAL HEADQUARTERS

main phone: 1-800-726-0110
international/main: 1-952-469-5424
sales: 1-800-726-0550
international/sales: 1-952-469-8240
 sales@despatch.com

www.despatch.com

8860 207th Street West
 Minneapolis, MN 55044 USA

Despatch
INDUSTRIES